

D3674

DAP EVO 6 Black

Passive 6.5" speaker set - black

DAP

EAN: 8717748443267



The DAP EVO 6 is a set of two 6.5-inch passive installation speakers for producing an excellent sound quality of up to 114 dB at one meter distance. With a peak power of 140 watt each, these 2-way Hi-Fi speakers have a high load capacity. It is therefore a perfect full-range audio solution for many locations such as restaurants, retail stores and even clubs.

The EVO 6 fits nicely into any indoor and outdoor location due to its elegant design (available in black and white), strong ABS housing and IP54 rating for protection against heavy rainfall, dust ingress and splash water.

Installation can be done quickly and easily with a terminal connectors and included brackets suitable for either horizontal or vertical mounting. Please note that an external amplifier is required. The DAP CA-4150 is a suitable device for amplifying the EVO 6 speaker set.

Special features:

- Full-range 2-way audio set for excellent Hi-Fi quality
- 70 W RMS, max SPL of 114 dB at 1 m each
- Suitable for outdoor use (IP54)
- Multi angled brackets (tiltable to up to 60 degrees)
- Quick and easy installation in either horizontal or vertical position
- Elegant ABS design available in black and white
- Perfect in combination with DAP CA-4150 Amplifier

Specifications:

Inputs

RMS Input Power	70 W
Peak Input Power	140 W
Passive Input Connection	Terminal

Audio Specifications

Speaker System	2-way
Speaker Sensitivity (1 W/1 m)	90 dB
Speaker Impedance	8 Ω
Maximum SPL at 1 m	114 dB
Frequency Response Minimum	50 Hz
Frequency Response Maximum	20000 Hz
Woofer Diameter	6.5"
Woofer Voice Coil Diameter	1.5"
Woofer Magnet Type	Ferrite
Compression Driver Diameter	1"
Compression Driver Voice Coil	1"
Compression Driver Magnet Type	Neodymium
Dispersion Angle (Horizontal)	110°
Dispersion Angle (Vertical)	90°

Mechanical Specifications

Height (mm)	300 mm
Width (mm)	195 mm
Depth (mm)	185 mm
Installation Depth (Excl. Connector)	245 mm
Material	ABS
Colour	Black
Weight	2.8 kg
IP Rating	IP54

Product Properties

Speaker Grille Material	Aluminium
-------------------------	-----------

Rigging

Mounting Options	Bracket
Mounting Orientations	Horizontal / Vertical

Thermal Specifications

Maximum Ambient Temperature	55°C
Minimum Ambient Temperature	-10°C

Included Items

Included Rigging	Bracket
------------------	---------

Downloads:

Manual

[D3674_MANUAL_GB_V1.pdf](#)

Declaration

[D3674_DoC_2019.pdf](#)

[D3674_UK_DoC_2021.pdf](#)