

GT1080e

Go big! Bright short throw home entertainment projector, great for sports



- **Create a 100" Full HD 1080p image from just over a metre away**
- **Lights on viewing – 3000 ANSI Lumens**
- **Easy connectivity - 2x HDMI and MHL support with built-in 10W speaker**
- **Lightweight and portable (carry bag included)**

Place your GT1080e on a coffee table and conveniently project a stunning 100 inch Full HD 1080p image from just over a metre from a flat surface or screen. Bright and versatile this portable projector is ideal for gamers with its low input latency, live sports and home entertainment any time of day. It even comes with a carry bag so you can take it round to a friend's house for a sports event, movie night or games marathon to provide you with the best big screen experience anywhere with a flat surface.



Specifications

Display/image	
Display technology	DLP
Resolution	1080p Full HD (1920x1080)
Brightness	3,000 lumens
Contrast ratio	25,000:1
Native aspect ratio	16:9
Aspect ratio - compatible	4:3
Keystone correction - vertical	+/-40°
Horizontal scan rate	15.375 ~ 91.146Khz
Vertical scan rate	24 ~ 85(120 for 3D)Hz
Uniformity	80%
Screen size	1.15m ~ 7.62m (45.3" ~ 300") diagonal
Lamp info	
Light source type	Lamp
Lamp watts	190
Lamp life hours (up to)	5000 (Bright), 6500 (Dynamic), 6000 (Eco)
Optical	
Throw ratio	0.49:1
Projection distance (m)	0.5m - 3.35m
Zoom type	Fixed
Focal length (mm)	7.42
Native offset	116%
Connectivity	
Connections	Inputs 1 x HDMI 1.4a 3D support + MHL, 1 x HDMI 1.4a 3D support Outputs 1 x Audio 3.5mm Control 1 x 3D sync, 1 x 12V trigger, 1 x mini USB service
General	
Noise level (typical)	26dB
PC compatibility	FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
2D compatibility	NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4.43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz)
3D compatibility	Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Full 3D
3D	Full 3D
Security	Security bar, Kensington Lock, Password protected interface
OSD / display languages	25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese
Operating conditions	5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m
Remote control	Backlit home remote
Speaker count	1
Watts per speaker	10W
In the box	Carry bag Lens cap AC power cord Remote control Battery Basic user manual
Input lag	33.00ms
Optional wireless models	WHD200
Power	
Power supply	100 ~ 240V, 50 ~ 60Hz
Power consumption (standby)	0.5W
Power consumption (min)	193W
Power consumption (max)	233W
Weight and dimensions	
Net weight	2.65kg
Dimensions (W x D x H) mm	315 x 224 x 114

