



## FGA-202

Order No.: 0251660

**Price upon request**

### PRODUCTINFOS

**Professional 2-channel line transformer,**

for reducing signal interference and hum loops.

- 2 inputs via balanced comb. jacks XLR/6.3 mm (600  $\Omega$ )
- 2 galvanically isolated XLR outputs (600  $\Omega$ ) with ground lift switch
- Frequency range: 20-20,000 Hz
- Robust metal housing with very good shielding qualities, suitable for stage applications
- Dimensions: 125 x 55 x 75 mm
- Weight: 650 g

### SOUNDCHECK 07/2007

on the FGA-102, FGA-202, LC-31, MC-31 and LSP-102:

“Every musician or sound engineer should have these little helpers in their toolbox. They impress by their unobtrusiveness. Both the robust metal housing and the functionality of these transformers allow to solve many problems on stage or in the studio at a reasonable price.”

**tools4music 06/2009**

on the LSP-102, LC-31, FGA-102, FGA-202, DIB-102

“Recommendable and fit for on-the-road applications. An attractively priced little audio aid, perfect for the 'ever accompanying' tool case.”

## TECHNICAL SPECIFICATIONS

### FGA-202

Description	transformer
Frequency range	20-20,000 Hz
Input impedance	600 $\Omega$
Output impedance	600 $\Omega$
Admiss. ambient temp.	0-40 °C
Dimensions	125 x 55 x 75 mm
Weight	650 g
Inputs	2 x comb. jack XLR/6.3 mm, bal.
Outputs	2 x XLR