

FLX0110 DAP FLX01- bal. XLR/M 3P to
XLR/F 3P X-type 10 m

10 m

DAP

EAN: 8717748338013



The FLX01 is a basic microphone cable for all-round use. The FLX01 has high quality specs, featuring X-type connectors, low noise, a wide dynamic range, high flexibility and is road-proof!

Specifications:

Electrical Specifications and Connections

Impedance	100 Ω
Connector 1	XLR 3P
Connector 2	XLR 3P
Cable Length	10 m
Pins	3
Conductor Resistance	80 Ω /km
Conductor Capacitance	65 pF/m
Capacity Inner Conduct. Shield/Inner Conduct.	78 pF/m
Outer Cable Diameter	6 mm
Outer Isolation Type	PVC

Mechanical Specifications

Weight	0.48 kg
IP Rating	IP20 (indoor use only)
Material	PVC
Colour	Black

Product Properties

Contact Type	Copper
1st Shield	Oxygen Free Copper
Filler Material	Cotton
Conductors	2

Thermal Specifications

Maximum Ambient Temperature	70°C
Minimum Ambient Temperature	-40°C

Product Accessories:

XXBL	Ring for X-type XLR Connector Blue
XXGR	Ring for X-type XLR Connector Green
XXOR	Ring for X-type XLR Connector Orange
XXRE	Ring for X-type XLR Connector Red
XXYE	Ring for X-type XLR Connector Yellow

Downloads:

Declaration

[FLX0110_DoC_2023.pdf](#)