

unbalanced zip cord patch cable low capacitance - PVC

- 0.22 mm² conductor cross section (AWG 24)
- compact construction (5.0 mm x 10.0 mm)
- low capacitance

PVC

A cable that raises the bar for superb signal transmission, both in quality home entertainment and in pro DJing. The IY204 actually consists of two individual cables in a ZIP Cord design that allows them to be easily separated. The cable can be used for applications such as a Y adapter - for example, from stereo mini-jack to dual cinch connectors. The inner conductor is of flexible stranded wire, with PE insulation of the cores to keep capacitance low and prevent loss of treble. An extra-dense copper spiral shield efficiently minimizes interference while retaining full flexibility and is easy to work with.

design

cond. construction	stranded bare copper, 7x 0.20 mm
cond. cross section	0.22 mm²
core arrangement	parallel, separable
outer jacket	PVC, matt

electric

conductor resistance	< 85 Ω/km
capacitance	
cond./shield	130 pF/m
insulation resistance	> 1 GΩ x km

mechanical & thermal characteristics

operating temperature	-25°C / +70°C
min. bending radius	
installed	4x overall diametre
mobile use	8x overall diameter
no hazardous substances	acc. to EU directivo RoHS 2011/65/EU from 08.06.2011
CE conformity	acc. to EU directivo LVD 2006/95/EG
flame retardancy	flame retardant acc. to IEC 60332-1-2

order code	cable color	weight kg/m	standard lengths m
IY205	black	0,06	30 / 50 / 100 / 200 / 300

technical specifications are subject to change

KLOTZ AIS GmbH
Johann-Sebastian-Bach-Str. 36
85591 Vaterstetten / Munich
Tel.: +49.(0)8106.308.0
Fax: +49.(0)8106.308.101
info@klotz-ais.com
klotz-ais.com