

**M1 professional microphone cable****2 x 0.22 mm² - white - PVC**

- 0.22 mm² conductor cross section (AWG 24)
- ultra-low capacitance 60 pF/m (18 pF/ft)
- bare copper spiral shield
- UV-resistant

PVC

When things hot up on stage, the iceRock Microphone Cable stays cool, doing its job with perfect reliability and ice-cold precision. The IR206 iceRock Prime Microphone Cable is an advanced version of our MY206 Professional Microphone Cable. Its rubber-like jacket made from special PVC keeps its flexibility even when temperatures soar. Additional cotton fibres maintain consistent capacitance through fluctuating conditions, avoiding interference. The extra-thick spiral shield provides effective screening. And to make sure the IR206 stays snow-white, we've added a special UV-resistant jacket to prevent yellowing. The IR 206 is thus the ideal cable for premium events with white stage sets or surface-mounted cabling in churches or other colour-sensitive environments.

design

cond. construction	stranded bare copper, 28 x 0.10 mm
cond. cross section	0.22 mm ²
insulation	polyethylene (PE)
core arrangement	2 cores + twisted cotton tracers
shielding	bare copper spiral shield
outer jacket	PVC, matt, UV resistant
overall diameter	6.15 mm

electric

conductor resistance	< 85 Ω/km
capacitance	
cond./cond.	60 pF/m
cond./shield	110 pF/m
insulation resistance	> 10 GΩ x km

mechanical & thermal characteristics

working temperature	-25°C / +70°C
min. bending radius	
installed	10x overall diameter
mobile use	5x overall diameter
no hazardous substances	acc. to EU directive RoHS 2011/65/EU from 08.06.2011
CE conformity	acc. to EU directive LVD 2006/95/EG
flame retardancy	acc. to IEC 60332-1-2
heat of combustion	760 kJ/m

order code	cable color	weight kg/m	standard lengths m
IR206	white	0,04	30 / 50 / 100 / 200 / 300 / 500

technical specifications are subject to change